

| | | | | | | | |
|---|--|--|--|---|--|---------------------------------------|--|
| APPLICATION FOR EQUIPMENT FREQUENCY ALLOCATION | | CLASSIFICATION UNCLASSIFIED | | DATE 04/09/2003 | | J/F 12/07253 | |
| | | | | | | Page 1 of 14 Pages | |
| DOD GENERAL INFORMATION | | | | | | | |
| TO Department of the Navy Naval Electromagnetic Spectrum Center CNO N61F Washington, DC 20350 | | | | FROM PEO-CU 47123 Buse Road, Unit IPT Patuxent River, MD 20670-1547 | | | |
| 1. APPLICATION TITLE (U) PREDATOR C-Band MAE UAV Medium Altitude Endurance Unmanned Aerial Vehicle | | | | | | | |
| 2. SYSTEM NOMENCLATURE (U) MAE UAV C-Band Line-of-Sight Command/Video Links | | | | | | | |
| 3. STAGE OF ALLOCATION (U) <input type="checkbox"/> a. STAGE 1 CONCEPTUAL <input type="checkbox"/> b. STAGE 2 EXPERIMENTAL <input type="checkbox"/> c. STAGE 3 DEVELOPMENTAL <input checked="" type="checkbox"/> d. STAGE 4 OPERATIONAL | | | | | | | |
| 4. FREQUENCY REQUIREMENTS a. FREQUENCY(IES) (U) 5250 MHz - 5850 MHz b. EMISSION DESIGNATORS (U) 560KF1D 17M0F9F (See Remarks) | | | | | | | |
| 5. TARGET STARTING DATE FOR SUBSEQUENT STAGES a. STAGE 2 (U) NA b. STAGE 3 (U) NA c. STAGE 4 (U) NA | | | | | | | |
| 6. EXTENT OF USE (U) Continuous during flight operations | | | | | | | |
| 7. GEOGRAPHICAL AREA FOR a. STAGE 2 (U) NA b. STAGE 3 (U) NA c. STAGE 4 (U) US&P; Korea; Contingency Operations in Central/South America | | | | | | | |
| 8. NUMBER OF UNITS a. STAGE 2 (U) NA b. STAGE 3 (U) NA c. STAGE 4 (U) 64 | | | | | | | |
| 9. NUMBER OF UNITS OPERATING SIMULTANEOUSLY IN THE SAME ENVIRONMENT(U) 6 | | | | | | | |
| 10. OTHER J/F 12 APPLICATION ID(S) TO BE (U) <input type="checkbox"/> a. SUPERSEDED <input type="checkbox"/> b. RELATED | | | | 11. IS THERE ANY OPERATIONAL REQUIREMENT AS DESCRIBED IN THE INSTRUCTIONS FOR PARAGRAPH 11? (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO <input type="checkbox"/> c. NAVAIL | | | |
| 12. NAMES AND TELEPHONE NUMBERS (U) | | | | | | | |
| a. PROGRAM MANAGER (b) (6) | | | | (1) COMMERCIAL (b) (6) | | (2) DSN (b) (6) | |
| b. PROJECT ENGINEER (b) (6) | | | | (1) COMMERCIAL | | (2) DSN | |
| 13. REMARKS (U) Item 4b: 4M72F1D, 88K3F1D Item 7c: Operation in conflict areas. | | | | | | | |
| DOWNGRADING INSTRUCTIONS | | | | | | J/F 12/07253 | |
| | | | | | | CLASSIFICATION UNCLASSIFIED | |

TRANSMITTER EQUIPMENT CHARACTERISTICS

| | | | |
|--|--|--|--|
| 1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) C-Band Transmitter, Model #1234211-SA-N | | 2. MANUFACTURER'S NAME (U) Sierra Monolithics, Inc. | |
| 3. TRANSMITTER INSTALLATION (U) Ground Data Terminal | | 4. TRANSMITTER TYPE (U) Digital FM Communications | |
| 5. TUNING RANGE (U) 5250 MHz - 5850 MHz | | 6. METHOD OF TUNING (U) PLL Synthesizer | |
| 7. RF CHANNELING CAPABILITY (U) 5.25 GHz, 1 MHz increments, 601 channels | | 8. EMISSION DESIGNATORS (U) 560KF1D (U) 88K3F1D (U) | |
| 9. FREQUENCY TOLERANCE (U) 20 ppm | | 12. EMISSION BANDWIDTH <input type="checkbox"/> CALCULATED <input checked="" type="checkbox"/> MEASURED | |
| 10. FILTER EMPLOYED (U) <input checked="" type="checkbox"/> a. YES <input type="checkbox"/> b. NO | | a. -3 dB (U) 340 KHz (U) 62.86 KHz (U) | |
| 11. SPREAD SPECTRUM (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO | | b. -20 dB (U) 420 KHz (U) 88.32 KHz (U) | |
| 13. MAXIMUM BIT RATE (U) 200 Kbps | | c. -40 dB (U) NA (U) 219.41 KHz (U) | |
| 14. MODULATION TECHNIQUES AND CODING (U) 15 bit randomized NRZ FSK data | | d. -60 dB (U) 1.2 MHz (U) 671.96 KHz (U) | |
| 16. PRE-EMPHASIS (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO | | e. OC-BW (U) 560 KHz (U) 88.32 KHz (U) | |
| 19. POWER | | 15. MAXIMUM MODULATION FREQUENCY (U) 100 KHz | |
| a. MEAN (U) 10 W (U) 10 W (U) | | 17. DEVIATION RATIO (U) 1.5 | |
| b. PEP (U) NA (U) NA (U) | | 18. PULSE CHARACTERISTICS | |
| 20. OUTPUT DEVICE (U) FET Transistor | | a. RATE (U) NA (U) (U) | |
| 22. SPURIOUS LEVEL (U) -65 dB | | b. WIDTH (U) NA (U) (U) | |
| 23. FCC TYPE ACCEPTANCE NO. (U) NA | | c. RISE TIME (U) NA (U) (U) | |
| | | d. FALL TIME (U) NA (U) (U) | |
| | | e. COMP RATIO (U) NA (U) (U) | |
| | | 21. HARMONIC LEVEL | |
| | | a. 2nd (U) -65 dB | |
| | | b. 3rd (U) -65 dB | |
| | | c. OTHER (U) -65 dB | |

24. REMARKS (U) Item 13: 19.2 Kbps/200 Kbps.

Item 17: 3 (19.2 Kbps)

| | |
|--|--|
| CLASSIFICATION <div style="text-align: center; font-weight: bold; font-size: 1.2em;">UNCLASSIFIED</div> | PAGE 3 |
| TRANSMITTER EQUIPMENT CHARACTERISTICS | |
| 1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) C-Band Transmitter, Model #1234211-SA-N | 2. MANUFACTURER'S NAME (U) Sierra Monolithics, Inc. |
| 3. TRANSMITTER INSTALLATION (U) MAE UAV (Predator) | 4. TRANSMITTER TYPE (U) FM Video/Data Communications |
| 5. TUNING RANGE (U) 5250 MHz - 5850 MHz | 6. METHOD OF TUNING (U) PLL Synthesizer |
| 7. RF CHANNELING CAPABILITY (U) 5.25 GHz, 1 MHz increments, 601 channels | 8. EMISSION DESIGNATORS (U) 17M0F9F (U) 4M72F1D (U) |
| 9. FREQUENCY TOLERANCE (U) 20 ppm | 12. EMISSION BANDWIDTH <div style="text-align: center;"> <input type="checkbox"/> CALCULATED <input checked="" type="checkbox"/> MEASURED </div> |
| 10. FILTER EMPLOYED (U) <input checked="" type="checkbox"/> a. YES <input type="checkbox"/> b. NO | a. -3 dB (U) 8.5 MHz (U) 2.8 MHz (U) |
| 11. SPREAD SPECTRUM (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO | b. -20 dB (U) 18.0 MHz (U) 20 MHz (U) |
| 13. MAXIMUM BIT RATE (U) 3.2 Mbps | c. -40 dB (U) NA (U) NA (U) |
| 14. MODULATION TECHNIQUES AND CODING (U) (See Remarks) | d. -60 dB (U) 46.2 MHz (U) 66 MHz (U) |
| 16. PRE-EMPHASIS (U) <input checked="" type="checkbox"/> a. YES <input type="checkbox"/> b. NO | e. OC-BW (U) 18.0 MHz (U) 4.7 MHz (U) |
| 19. POWER | 15. MAXIMUM MODULATION FREQUENCY (U) 8.0 MHz |
| a. MEAN (U) 10 W (U) 10 W (U) | 17. DEVIATION RATIO (U) (See Remarks) |
| b. PEP (U) NA (U) NA (U) | 18. PULSE CHARACTERISTICS |
| 20. OUTPUT DEVICE (U) FET Transistor | a. RATE (U) NA (U) NA (U) |
| 22. SPURIOUS LEVEL (U) -65 dB | b. WIDTH (U) NA (U) NA (U) |
| 23. FCC TYPE ACCEPTANCE NO. (U) NA | c. RISE TIME (U) NA (U) NA (U) |
| 24. REMARKS (U) | d. FALL TIME (U) NA (U) NA (U) |
| Item 14: FM Video with 6.8 and 7.5 MHz Telemetry Subcarriers (17M0F9F), or FSK Data with 6.8 and 7.5 MHz carriers not utilized (4M72F1D). | e. COMP RATIO (U) NA (U) NA (U) |
| Item 16: Standard NTSC pre-emphasis is employed. | 21. HARMONIC LEVEL |
| Item 17: Deviation Ratio 0.8 for 17M0F9F 0.625 for 4M72F1D | a. 2nd (U) -65 dB |
| | b. 3rd (U) -65 dB |
| | c. OTHER (U) -65 dB |

RECEIVER EQUIPMENT CHARACTERISTICS

1. NOMENCLATURE, MANUFACTURER'S MODEL NO.

(U) C-Band Receiver, Model #1235110N

2. MANUFACTURER'S NAME

(U) Sierra Monolithics, Inc.

3. RECEIVER INSTALLATION

(U) MAE UAV (Predator)

4. RECEIVER TYPE

(U) Dual Conversion Superheterodyne

5. TUNING RANGE

(U) 5250 MHz - 5850 MHz

6. METHOD OF TUNING

(U) PLL Synthesizer

7. RF CHANNELING CAPABILITY

(U) 5.25 GHz, 1 MHz increments, 601 channels

8. EMISSION DESIGNATORS

(U) 560KF1D 88K3F1D

9. FREQUENCY TOLERANCE

(U) 20 ppm

11. RF SELECTIVITY

☐

CALCULATED

☒

MEASURED

10. IF SELECTIVITY

1st (U)

2nd (U)

3rd (U)

a. -3 dB

35 MHz

1 MHz

NA

b. -20 dB

55 MHz

3.2 MHz

NA

c. -60 dB

115 MHz

4 MHz

NA

a. -3 dB

(U) 303 MHz

b. -20 dB

(U) 375 MHz

c. -60 dB

(U) 525 MHz

d. Preselection Type

(U) (See Remarks)

12. IF FREQUENCY

a. 1st (U)

954 MHz

b. 2nd (U)

70 MHz

c. 3rd (U)

NA

13. MAXIMUM POST DETECTION FREQUENCY

(U) 150 KHz

14. MINIMUM POST DETECTION FREQUENCY

(U) NA

16. MAXIMUM BIT RATE

(U) 200 Kbps

15. OSCILLATOR TUNED

1st (U)

2nd (U)

3rd (U)

a. ABOVE TUNED FREQUENCY

X

b. BELOW TUNED FREQUENCY

X

c. EITHER ABOVE OR BELOW
THE FREQUENCY

17. SENSITIVITY

a. SENSITIVITY (U) - 98 dBm

b. CRITERIA (U) 1×10^{-6} BER

c. NOISE FIG (U) 2 dB

d. NOISE TEMP (U) NA

18. DE-EMPHASIS

(U) ☐ a. YES☒ b. NO

19. IMAGE REJECTION

(U) 60 dB

20. SPURIOUS REJECTION

(U) 50 dB

21. REMARKS (U) Item 11d: 10 section cavity bandpass filter.

RECEIVER EQUIPMENT CHARACTERISTICS

1. NOMENCLATURE, MANUFACTURER'S MODEL NO.

(U) C-Band Receiver, Model #1235110N

2. MANUFACTURER'S NAME

(U) Sierra Monolithics, Inc.

3. RECEIVER INSTALLATION

(U) Ground Data Terminal

4. RECEIVER TYPE

(U) Dual Conversion Superheterodyne

5. TUNING RANGE

(U) 5250 MHz - 5850 MHz

6. METHOD OF TUNING

(U) PLL Synthesizer

7. RF CHANNELING CAPABILITY

(U) 5.25 GHz, 1 MHz increments, 601 channels

8. EMISSION DESIGNATORS

(U) 17M0F9F 4M72F1D

9. FREQUENCY TOLERANCE

(U) 20 ppm

11. RF SELECTIVITY

☐

CALCULATED

☒

MEASURED

10. IF SELECTIVITY

1st (U)

2nd (U)

3rd (U)

a. -3 dB

35 MHz

20 MHz

NA

b. -20 dB

55 MHz

22.5 MHz

NA

c. -60 dB

115 MHz

28 MHz

NA

a. -3 dB

(U) 303 MHz

b. -20 dB

(U) 375 MHz

c. -60 dB

(U) 525 MHz

d. Preselection Type

(U) (See Remarks)

12. IF FREQUENCY

a. 1st (U)

954 MHz

b. 2nd (U)

70 MHz

c. 3rd (U)

NA

13. MAXIMUM POST DETECTION FREQUENCY

(U) 8.0 MHz

14. MINIMUM POST DETECTION FREQUENCY

(U) NA

16. MAXIMUM BIT RATE

(U) 3.2 Mbps

15. OSCILLATOR TUNED

1st (U)

2nd (U)

3rd (U)

a. ABOVE TUNED FREQUENCY

X

b. BELOW TUNED FREQUENCY

X

c. EITHER ABOVE OR BELOW
THE FREQUENCY

17. SENSITIVITY

a. SENSITIVITY (U) (See Remarks)

b. CRITERIA (U) (See Remarks)

c. NOISE FIG (U) 2 dB

d. NOISE TEMP (U) NA

18. DE-EMPHASIS

(U)

☒

a. YES

☐

b. NO

19. IMAGE REJECTION

(U) 60 dB

20. SPURIOUS REJECTION

(U) 50 dB

21. REMARKS (U) Item 11d: 10 section cavity bandpass filter.

Item 17: -84 dBm for 23 dB S/N and 17M0F9F
-86 dBm for 1×10^{-6} BER and 4M72F1D.

CLASSIFICATION

UNCLASSIFIED

PAGE 6

ANTENNA EQUIPMENT CHARACTERISTICS

| | |
|---|--|
| 1. (U) <input type="checkbox"/> a. TRANSMITTING <input type="checkbox"/> b. RECEIVING <input checked="" type="checkbox"/> c. TRANSMITTING AND RECEIVING | |
| 2. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) GCS Acquisition Horn, Model #15921 | 3. MANUFACTURER'S NAME (U) Technical Systems Associates |
| 4. FREQUENCY RANGE (U) 5250 MHz - 5850 MHz | 5. TYPE (U) Monopulse Horn |
| 6. POLARIZATION (U) Vertical | 7. SCAN CHARACTERISTICS |
| 8. GAIN | a. TYPE (U) MECHANICAL |
| a. MAIN BEAM (U) 15.0 dBi | b. VERTICAL SCAN (U) Manual |
| b. 1st MAJOR SIDE LOBE (U) 2.0 dBi @ 44 deg | (1) Max Elev (U) 30 deg |
| 9. BEAMWIDTH | (2) Min Elev (U) -10 deg |
| a. HORIZONTAL (U) 30 deg | (3) Scan Rate (U) NA |
| b. VERTICAL (U) 30 deg | c. HORIZONTAL SCAN (U) Mechanical |
| | (1) Sector Scanned (U) 360 |
| | (2) Scan Rate (U) 45 deg/sec, <11 scans/minute |
| | d. SECTOR BLANKING (U) <input type="checkbox"/> (1) YES <input checked="" type="checkbox"/> (2) NO |

10. REMARKS (U)

Item 7b: The horn is normally adjusted to be 20 degrees above the horizon.

CLASSIFICATION

UNCLASSIFIED

J/F 12/07253

CLASSIFICATION

UNCLASSIFIED

PAGE 7

ANTENNA EQUIPMENT CHARACTERISTICS

| | |
|---|--|
| 1. (U) <input type="checkbox"/> a. TRANSMITTING <input type="checkbox"/> b. RECEIVING <input checked="" type="checkbox"/> c. TRANSMITTING AND RECEIVING | |
| 2. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) GCS 6' Dish Antenna, Model #16616 | 3. MANUFACTURER'S NAME (U) Technical Systems Associates |
| 4. FREQUENCY RANGE (U) 5250 MHz - 5850 MHz | 5. TYPE (U) (See Remarks) |
| 6. POLARIZATION (U) Vertical | 7. SCAN CHARACTERISTICS |
| 8. GAIN | a. TYPE (U) MECHANICAL |
| a. MAIN BEAM (U) 34.5 dBi | b. VERTICAL SCAN (U) Adjustable |
| b. 1st MAJOR SIDE LOBE (U) 14.5 dBi @ 3.5 deg | (1) Max Elev (U) 30 deg |
| 9. BEAMWIDTH | (2) Min Elev (U) -10 deg |
| a. HORIZONTAL (U) 2.2 deg | (3) Scan Rate (U) NA |
| b. VERTICAL (U) 2.2 deg | c. HORIZONTAL SCAN (U) Mechanical |
| | (1) Sector Scanned (U) 360 |
| | (2) Scan Rate (U) 45 deg/sec, <11 scans/minute |
| | d. SECTOR BLANKING (U) <input type="checkbox"/> (1) YES <input checked="" type="checkbox"/> (2) NO |

10. REMARKS (U)

Item 5: 1.83 Meter cosecant-squared reflector with monopulse feed.

CLASSIFICATION

UNCLASSIFIED

J/F 12/07253

CLASSIFICATION

UNCLASSIFIED

PAGE 8

ANTENNA EQUIPMENT CHARACTERISTICS

1. (U)

☐

a. TRANSMITTING

☐

b. RECEIVING

☒

c. TRANSMITTING AND RECEIVING

2. NOMENCLATURE, MANUFACTURER'S MODEL NO.

(U) GCS Omni Antenna, Model #10171

3. MANUFACTURER'S NAME

(U) Technical Systems Associates

5. TYPE (U) Stacked Dipole Array

4. FREQUENCY RANGE

(U) 5250 MHz - 5850 MHz

7. SCAN CHARACTERISTICS

a. TYPE (U) FIXED

6. POLARIZATION

(U) Vertical

b. VERTICAL SCAN (U) NA

(1) Max Elev (U)

8. GAIN

a. MAIN BEAM

(U) 6 dBi

(2) Min Elev (U)

(3) Scan Rate (U)

b. 1st MAJOR SIDE LOBE

(U) NA

c. HORIZONTAL SCAN (U) NA

(1) Sector Scanned (U)

9. BEAMWIDTH

a. HORIZONTAL

(U) 360 deg

(2) Scan Rate (U)

b. VERTICAL

(U) 30 deg

d. SECTOR BLANKING (U) ☐ (1) YES ☒ (2) NO

10. REMARKS (U)

None.

CLASSIFICATION

UNCLASSIFIED

J/F 12/07253

CLASSIFICATION

UNCLASSIFIED

PAGE 9

ANTENNA EQUIPMENT CHARACTERISTICS

| | |
|---|--|
| 1. (U) <input type="checkbox"/> a. TRANSMITTING <input type="checkbox"/> b. RECEIVING <input checked="" type="checkbox"/> c. TRANSMITTING AND RECEIVING | |
| 2. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) MAE UAV Omni, Model #702653-1 | 3. MANUFACTURER'S NAME (U) TECOM Industries, Inc. |
| 4. FREQUENCY RANGE (U) 5250 MHz - 5850 MHz | 5. TYPE (U) Stacked Dipole Array |
| 6. POLARIZATION (U) Vertical | 7. SCAN CHARACTERISTICS |
| 8. GAIN | a. TYPE (U) FIXED |
| a. MAIN BEAM (U) 3 dBi | b. VERTICAL SCAN (U) NA |
| b. 1st MAJOR SIDE LOBE (U) NA | (1) Max Elev (U) |
| 9. BEAMWIDTH | (2) Min Elev (U) |
| a. HORIZONTAL (U) 360 deg | (3) Scan Rate (U) |
| b. VERTICAL (U) 25 deg | c. HORIZONTAL SCAN (U) NA |
| | (1) Sector Scanned (U) |
| | (2) Scan Rate (U) |
| | d. SECTOR BLANKING (U) <input type="checkbox"/> (1) YES <input checked="" type="checkbox"/> (2) NO |

10. REMARKS (U)

None.

CLASSIFICATION

UNCLASSIFIED

J/F 12/07253

CLASSIFICATION

UNCLASSIFIED

PAGE 10

ANTENNA EQUIPMENT CHARACTERISTICS

| | |
|---|--|
| 1. (U) <input type="checkbox"/> a. TRANSMITTING <input type="checkbox"/> b. RECEIVING <input checked="" type="checkbox"/> c. TRANSMITTING AND RECEIVING | |
| 2. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) MAE UAV Horn Antenna, Model #11572 | 3. MANUFACTURER'S NAME (U) Technical Associates, Inc. |
| 4. FREQUENCY RANGE (U) 5250 MHz - 5850 MHz | 5. TYPE (U) Lensed Horn |
| 6. POLARIZATION (U) Vertical | 7. SCAN CHARACTERISTICS |
| 8. GAIN | a. TYPE (U) MECHANICAL |
| a. MAIN BEAM (U) 15.0 dBi | b. VERTICAL SCAN (U) Fixed, Adjustable |
| b. 1st MAJOR SIDE LOBE (U) -5 dBi @ 44 deg | (1) Max Elev (U) 30 deg |
| 9. BEAMWIDTH | (2) Min Elev (U) -30 deg |
| a. HORIZONTAL (U) 30 deg | (3) Scan Rate (U) NA |
| b. VERTICAL (U) 30 deg | c. HORIZONTAL SCAN (U) Mechanical |
| | (1) Sector Scanned (U) 360 |
| | (2) Scan Rate (U) 45 deg/sec, <11 scans/minute |
| | d. SECTOR BLANKING (U) <input type="checkbox"/> (1) YES <input checked="" type="checkbox"/> (2) NO |

10. REMARKS (U)

None.

CLASSIFICATION

UNCLASSIFIED

J/F 12/07253

ANTENNA EQUIPMENT CHARACTERISTICS

| | |
|---|--|
| 1. (U) <input type="checkbox"/> a. TRANSMITTING <input type="checkbox"/> b. RECEIVING <input checked="" type="checkbox"/> c. TRANSMITTING AND RECEIVING | |
| 2. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) MAE UAV Monopole Stub, #702-653-3 | 3. MANUFACTURER'S NAME (U) TECOM Industries, Inc. |
| 4. FREQUENCY RANGE (U) 5250 MHz - 5850 MHz | 5. TYPE (U) 1/4 Wavelength Monopole Stub |
| 6. POLARIZATION (U) Vertical | 7. SCAN CHARACTERISTICS |
| 8. GAIN | a. TYPE (U) FIXED |
| a. MAIN BEAM (U) 0.3 dBi | b. VERTICAL SCAN (U) NA |
| b. 1st MAJOR SIDE LOBE (U) NA | (1) Max Elev (U) |
| 9. BEAMWIDTH | (2) Min Elev (U) |
| a. HORIZONTAL (U) 360 deg | (3) Scan Rate (U) |
| b. VERTICAL (U) 55 deg | c. HORIZONTAL SCAN (U) NA |
| | (1) Sector Scanned (U) |
| | (2) Scan Rate (U) |
| | d. SECTOR BLANKING (U) <input type="checkbox"/> (1) YES <input checked="" type="checkbox"/> (2) NO |

10. REMARKS (U)

General: AN/URY-1/2/3/4 R-Cubed Units all have the same antenna equipment characteristics.

| | | |
|---|---|---|
| APPLICATION FOR SPECTRUM REVIEW | CLASSIFICATION UNCLASSIFIED | PAGE 12 |
| NTIA GENERAL INFORMATION | | |
| 1. APPLICATION TITLE (U) PREDATOR C-Band MAE UAV Medium Altitude Endurance Unmanned Aerial Vehicle | | |
| 2. SYSTEM NOMENCLATURE (U) MAE UAV C-Band Line-of-Sight Command/Video Links | | |
| 3. STAGE OF ALLOCATION (U) <input type="checkbox"/> a. STAGE 1 CONCEPTUAL <input type="checkbox"/> b. STAGE 2 EXPERIMENTAL <input type="checkbox"/> c. STAGE 3 DEVELOPMENTAL <input checked="" type="checkbox"/> d. STAGE 4 OPERATIONAL | | |
| 4. FREQUENCY REQUIREMENTS a. FREQUENCY(IES) (U) 5250 MHz - 5850 MHz 5250 MHz - 5850 MHz 5250 MHz - 5850 MHz b. EMISSION DESIGNATORS (U) 560KF1D 17M0F9F 4M72F1D | | |
| 5. PURPOSE OF SYSTEM, OPERATIONAL AND SYSTEM CONCEPTS (U) (WARTIME USE) <input checked="" type="checkbox"/> a. YES <input type="checkbox"/> b. NO Provide command and control of unmanned aerial vehicle, transmit payload imagery and system telemetry data. | | |
| 6. INFORMATION TRANSFER REQUIREMENTS (U) 19.2/200 Kbps FSK uplink; FM analog video with 19.2 kbps on subcarriers or 3.2 Mbps FSK data downlink | | |
| 7. ESTIMATED INITIAL COST OF THE SYSTEM (U) \$75k per aerial vehicle system | | |
| 8. TARGET DATE FOR | | |
| a. APPLICATION APPROVAL (U) 03/01/1998 | b. SYSTEM ACTIVATION (U) 04/01/1998 | c. SYSTEM TERMINATION (U) 12/31/2015 |
| 9. SYSTEM RELATIONSHIP AND ESSENTIALITY (U) This system controls the MAE UAV "PREDATOR" within Line-of-Sight, and is critical to the mission. | | |
| 10. REPLACEMENT INFORMATION (U) None | | |
| 11. RELATED ANALYSIS AND/OR TEST DATA (U) None | | |
| 12. NUMBER OF MOBILE UNITS (U) 64 | | |
| 13. GEOGRAPHICAL AREA FOR | | |
| a. STAGE 2 (U) NA | | |
| b. STAGE 3 (U) NA | | |
| c. STAGE 4 (U) US&P; Korea; Contingency operations in Central/South America | | |
| 14. LINE DIAGRAM (U) See Page(s) 12 | | 15. SPACE SYSTEMS (U) See Page(s) NA |
| 16. TYPE OF SERVICE(S) FOR STAGE 4 (U) Aeronautical Mobile Mobile | | 17. STATION CLASS(ES) FOR STAGE 4 (U) FAD MOEA |
| 18. REMARKS (U) Item 4b: The transmitters and receivers are configurable via software setup for either 88K3F1D, 560KF1D, 4M72F1D, or 17M0F9F. Item 13c: Operations in conflict areas. | | |
| DOWNGRADING INSTRUCTIONS | | J/F 12/07253 CLASSIFICATION UNCLASSIFIED |

UNCLASSIFIED

MILITARY COMMUNICATIONS ELECTRONICS BOARD (MCEB)
EQUIPMENT FREQUENCY ALLOCATION GUIDANCE

Military Department: Navy, Air Force
Equipment:

PREDATOR C-Band MAE UAV Medium Altitude Endurance Unmanned Aerial
Vehicle
Stage: 4- Operational

Section 1: ENCLOSURE

1. J/F 12/07253, 09 APR 2003

Section 2: OPERATING CHARACTERISTICS FOR WHICH SUPPORT IS CERTIFIED

Frequency: 5250-5850 MHz

Emissions: (a)88K3F1D, 560KF1D; (b)4M72F1D, 17M0F9F.

Power (Mean): 10.0 WATTS

Type of Services: (a)Mobile (Aeronautical Mobile); (b)Mobile

Operating Locations: Phoenix, AZ (only ground Testing); Ft. Huachuca,
AZ; Yuma Proving Grounds, AZ; El Mirage Flight Test Facility, Adelanto,
CA; Edwards AFB, CA (including China Lake, CA); Aeronautical Systems, San
Diego, CA; Marina, CA;
Camp Roberts, CA; San Clemente Island, CA; San Nicholas Island, CA; NTC
Fort Irwin, CA; NAS Key West, FL; MacDill AFB, FL; Kauai, HI; Fort Polk,
LA; Roswell, NM; Tinker AFB, OK; Fort Sill, OK; Nellis AFB, NV; Indian
Springs, NV; Nevada Test Site, NV; Fallon, NV; El Paso, TX; Langley AFB,
VA

Section 3: MCEB GUIDANCE

1. The enclosed application is approved for operational use at the above
locations subject to the guidance provided in the following paragraphs.

2. For the intended use in the Aeronautical Mobile and Aeronautical
Fixed service, the subject equipment is not in accordance with the US and
ITU Table of Frequency Allocations over its tuning range. Operations
will be on an unprotected, non-interference basis to the established
services at the above locations.

3. The provisions of NTIA manual Sections 5.2 and 5.3.3 are considered
applicable to the operation of the subject equipment. Based on the
information provided, the subject equipment does comply with NTIA Manual
Sections 5.2 requirement for frequency tolerances and unwanted emissions
and, Section 5.3.3 requirement for spurious, and harmonics emission
levels, unwanted emissions bandwidth and receiver's IF selectivity and
spurious rejection. In any instance of harmful interference caused by
nonconformance with these provisions, the responsibility for eliminating
the harmful interference normally shall rest with the agency operating in
nonconformance.

4. The subject equipment does not comply with the requirements of

MIL-STD-461E for harmonic levels. Compliance is not mandatory but the standard may be used as a design objective.

5. Frequency assignments request must be submitted using Standard Frequency Action Format (SFAF) and coordinated with the cognizant area frequency coordinator in accordance with ACP 190 US SUPP-1 (C), Guide to Frequency Planning, prior to activation.

6. Coordination with the NTIA Spectrum Planning Subcommittee was requested.

7. Operational use within the appropriate theater commands outside the United States has not been approved. Approval for operational use in the intended deployment area requires appropriate CINC's statement(s) that the subject system has been deemed frequency supportable.

Steering Member
ESG Working Group
MCEB Frequency Panel

APPROVAL SIGNATURE Date: 07 May 2003

IRAC DOC #: 32666/1
SPS #: 13432

Downgrading Instructions
Classified by: NA
Declassify on: NA

Distribution: J-12 Holders
MCEB J-12 Number: J/F 12/07253/1
UNCLASSIFIED